

# **EXPRESS NAIL CEILING CLIPS - ZINC PLATED**

### PRODUCT DESCRIPTION

- Express nail with eye for lightweight applications in concrete and masonry
- The nail sleeve is hammered in and expands its entire length in the hole

# **GENERAL APPLICATIONS AND USES**

- Lightweight suspended ceilings
- Wire hangers





#### **BASE MATERIAL: IDEAL FOR MASONRY**
















\* Also suitable for


		<b>&gt;&gt;</b> Ø			1	
Cat No.	Description	Drill Dia. [mm]	Length [mm]	Eye Diameter [mm]	Box Quantity	Carton Quantity
DFM3130500	Express Nail-Ceiling Clip 8mmx42mm - Zinc Plated	8 x	42	5	1×100	8×100

### **INSTALLATION INSTRUCTIONS**










# **RECOMMENDED LOAD**

RECOMMENDED LOAD, UNCRACK			
Description	h <sub>nom</sub> [mm]	h <sub>1</sub> [mm]	N <sub>rec</sub> [kN]
Express Nail Ceiling Clip	18	30	0.20

$$\frac{N_{Rk}}{\gamma_{M} \cdot \gamma_{F} = N_{rec}}$$

$$\frac{\gamma_{M} = 2.1}{\gamma_{F} = 1.4}$$

Recommended loads are based on the simplified design method according to ETAG 001, Annex C and are valid for one anchor. For Design loads multiply by the factor  $\gamma_{\rm F}.$ 



# **MATERIAL SPECIFICATION**

Sleeve: AISI steel 1050, hardened